

Indiana Department of Environmental Management

We make Indiana a cleaner, healthier place to live.

Frank O'Bannon
Governor

Lori F. Kaplan Commissioner

100 North Senate Avenue
P. O. Box 6015
Indianapolis, Indiana 46206-6015
(317) 232-8603
(800) 451-6027
www.in.gov/idem

PART 70 OPERATING PERMIT RENEWAL OFFICE OF AIR QUALITY

Masonite Door Corporation 305 Industrial Parkway Richmond, Indiana 47374

(herein known as the Permittee) is hereby authorized to operate subject to the conditions contained herein, the source described in Section A (Source Summary) of this permit.

This permit is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-7 as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17.

Operation Permit No.: T177-16192-00068

Issued by: Original Signed
Janet G. McCabe, Assistant Commissioner
Office of Air Quality

Issuance Date July 23 2003

Expiration Date: July 23 2008

Please

TABLE OF CONTENTS

A SOURCE SUMMARY

- A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)] [326 IAC 2-7-1(22)]
- A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)] [326 IAC 2-7-5(15)
- A.3 Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]
- A.4 Part 70 Permit Applicability [326 IAC 2-7-2]

B GENERAL CONDITIONS

- B.1 Definitions [326 IAC 2-7-1]
- B.2 Permit Term [326 IAC 2-7-5(2)] [326 IAC 2-1.1-9.5]
- B.3 Enforceability [326 IAC 2-7-7]
- B.4 Termination of Right to Operate [326 IAC 2-7-10] [326 IAC 2-7-4(a)]
- B.5 Severability [326 IAC 2-7-5(5)]
- B.6 Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]
- B.7 Duty to Supplement and Provide Information [326 IAC 2-7-4(b)] [326 IAC 2-7-5(6)(E)] [326 IAC 2-7-6(6)]
- B.8 Compliance with Permit Conditions [326 IAC 2-7-5(6)(A)] [326 IAC 2-7-5(6)(B)]
- B.9 Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)(C)]
- B.10 Annual Compliance Certification [326 IAC 2-7-6(5)]
- B.11 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3)and (13)][326 IAC 2-7-6(1)and(6)] [326 IAC 1-6-3]
- B.12 Emergency Provisions [326 IAC 2-7-16]
- B.13 Permit Shield [326 IAC 2-7-15] [326 IAC 2-7-20] [326 IAC 2-7-12]
- B.14 Prior Permits Superseded [326 IAC 2-1.1-9.5]
- B.15 Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]
- B.16 Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-7-5(6)(C)] [326 IAC 2-7-8(a)] [326 IAC 2-7-9]
- B.17 Permit Renewal [326 IAC 2-7-4]
- B.18 Permit Amendment or Modification [326 IAC 2-7-11][326 IAC 2-7-12]
- B.19 Permit Revision Under Economic Incentives and Other Programs [326 IAC 2-7-5(8)] [326 IAC 2-7-12(b)(2)]
- B.20 Operational Flexibility [326 IAC 2-7-20] [326 IAC 2-7-10.5]
- B.21 Source Modification Requirement [326 IAC 2-7-10.5]
- B.22 Inspection and Entry [326 IAC 2-7-6] [IC 13-14-2-2]
- B.23 Transfer of Ownership or Operation [326 IAC 2-7-11]
- B.24 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)][326 IAC 2-1.1-7]

C SOURCE OPERATION CONDITIONS

Emission Limitations and Standards [326 IAC 2-7-5(1)]

- C.1 Particulate Matter Emission Limitations For Processes with Process Weight Rates [40 CFR Subpart P] [326 IAC 6-3-2]
- C.2 Opacity [326 IAC 5-1]
- C.3 Open Burning [326 IAC 4-1] [IC 13-17-9]
- C.4 Incineration [326 IAC 4-2] [326 IAC 9-1-2]
- C.5 Fugitive Dust Emissions [326 IAC 6-4]
- C.6 Operation of Equipment [326 IAC 2-7-6(6)]
- C.7 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]

Testing Requirements [326 IAC 2-7-6(1)]

C.8 Performance Testing [326 IAC 3-6]

Compliance Requirements [326 IAC 2-1.1-11]

C.9 Compliance Requirements [326 IAC 2-1.1-11]

Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]

- C.10 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]
- C.11 Monitoring Methods [326 IAC 3]

Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]

- C.12 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]
- C.13 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68.215]
- C.14 Compliance Response Plan Preparation, Implementation, Records, and Reports [326 IAC 2-7-5] [326 IAC 2-7-6]
- C.15 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5]

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

- C.16 Emission Statement [326 IAC 2-7-5(3)(C)(iii)] [326 IAC 2-7-5(7)] [326 IAC 2-7-19(c)]
- C.17 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6]
- C.18 General Reporting Requirements [326 IAC 2-7-5(3)(C)] [326 IAC 2-1.1-11]

Stratospheric Ozone Protection

C.19 Compliance with 40 CFR 82 and 326 IAC 22-1

MACT Application Submittal Requirement

C.20 Application Requirements for Section 112(j) of the Clean Air Act [40 CFR 63.52(e)] [40 CFR 63.56(a)] [40 CFR 63.9(b)] [326 IAC 2-7-12]

D.1 FACILITY OPERATION CONDITIONS - Two (2) surface coating silos

Emission Limitations and Standards [326 IAC 2-7-5(1)]

- D.1.1 Volatile Organic Compounds (VOC) [326 IAC 8-6]
- D.1.2 Particulate Matter (PM) [40 CFR 52 Subpart P]
- D.1.3 Particulate [326 IAC 6-3-2(d)]
- D.1.4 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.1.5 Monitoring

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.1.6 Record Keeping Requirements

Certification

Emergency Occurrence Report

Quarterly Deviation and Compliance Monitoring Report

Masonite Door Corporation Richmond, Indiana

Permit Reviewer: Jed D. Wolkins

SECTION A

SOURCE SUMMARY

This permit is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ). The information describing the source contained in conditions A.1 through A.3 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this permit pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)] [326 IAC 2-7-1(22)]

The Permittee owns and operates a stationary metal door manufacturing plant.

Responsible Official: Site Manager

Source Address: 305 Industrial Parkway, Richmond, Indiana 47374

Mailing Address: P.O. Box 667, Richmond, Indiana 47374

General Source Phone Number: (765)962-8515 SIC Code: 3442 County Location: Wayne

Source Location Status: Attainment for all criteria pollutants

Source Status: Part 70 Permit Program

Minor Source, under PSD;

Major Source, Section 112 of the Clean Air Act

A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)]

[326 IAC 2-7-5(15)]

This stationary source consists of the following emission units and pollution control devices:

Two (2) surface coating silos, identified as Paint 1 and Paint 2, both constructed after July 1977 and before January 1980, each with a maximum capacity of 12 feet of door per minute, both utilizing the electrostatic disc method of paint application, both connected to an auxiliary natural gas oven, both using dry filters as control, and exhausting to vents C1 and C2, respectively.

A.3 Specifically Regulated Insignificant Activities [326 IAC 2-7-1(21)] [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]

This stationary source does not currently have any insignificant activities, as defined in 326 IAC 2-7-1 (21) that have applicable requirements.

A.4 Part 70 Permit Applicability [326 IAC 2-7-2]

This stationary source is required to have a Part 70 permit by 326 IAC 2-7-2 (Applicability) because it is a major source, as defined in 326 IAC 2-7-1(22).

SECTION B

GENERAL CONDITIONS

B.1 Definitions [326 IAC 2-7-1]

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations (IC 13-11, 326 IAC 1-2 and 326 IAC 2-7) shall prevail.

B.2 Permit Term [326 IAC 2-7-5(2)] [326 IAC 2-1.1-9.5]

This permit is issued for a fixed term of five (5) years from the issuance date of this permit, as determined in accordance with IC 4-21.5-3-5(f) and IC 13-15-5-3. Subsequent revisions, modifications, or amendments of this permit do not affect the expiration date.

B.3 Enforceability [326 IAC 2-7-7]

Unless otherwise stated, all terms and conditions in this permit, including any provisions designed to limit the source's potential to emit, are enforceable by IDEM, the United States Environmental Protection Agency (U.S. EPA), and by citizens in accordance with the Clean Air Act.

B.4 Termination of Right to Operate [326 IAC 2-7-10] [326 IAC 2-7-4(a)]

The Permittee's right to operate this source terminates with the expiration of this permit unless a timely and complete renewal application is submitted at least nine (9) months prior to the date of expiration of the source's existing permit, consistent with 326 IAC 2-7-3 and 326 IAC 2-7-4(a).

B.5 Severability [326 IAC 2-7-5(5)]

The provisions of this permit are severable; a determination that any portion of this permit is invalid shall not affect the validity of the remainder of the permit.

B.6 Property Rights or Exclusive Privilege [326 IAC 2-7-5(6)(D)]

This permit does not convey any property rights of any sort or any exclusive privilege.

B.7 Duty to Supplement and Provide Information [326 IAC 2-7-4(b)] [326 IAC 2-7-5(6)(E)] [326 IAC 2-7-6(6)]

(a) The Permittee, upon becoming aware that any relevant facts were omitted or incorrect information was submitted in the permit application, shall promptly submit such supplementary facts or corrected information to:

Indiana Department of Environmental Management Permits Branch, Office of Air Quality 100 North Senate Avenue, P. O. Box 6015 Indianapolis, Indiana 46206-6015

The submittal by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) The Permittee shall furnish to IDEM, OAQ, within a reasonable time, any information that IDEM, OAQ may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit, or to determine compliance with this permit. The submittal by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34). Upon request, the Permittee shall also furnish to IDEM, OAQ copies of records required to be kept by this permit.
- (c) For information furnished by the Permittee to IDEM, OAQ, the Permittee may include a claim of confidentiality in accordance with 326 IAC 17.1. When furnishing copies of requested records directly to U. S. EPA, the Permittee may assert a claim of confidentiality in accordance with 40 CFR 2, Subpart B.

B.8 Compliance with Permit Conditions [326 IAC 2-7-5(6)(A)] [326 IAC 2-7-5(6)(B)]

- (a) The Permittee must comply with all conditions of this permit. Noncompliance with any provisions of this permit is grounds for:
 - (1) Enforcement action;
 - (2) Permit termination, revocation and reissuance, or modification; or
 - (3) Denial of a permit renewal application.
- (b) Noncompliance with any provision of this permit, except any provision specifically designated as not federally enforceable, constitutes a violation of the Clean Air Act.
- (c) It shall not be a defense for the Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.
- (d) An emergency does constitute an affirmative defense in an enforcement action provided the Permittee complies with the applicable requirements set forth in Section B, Emergency Provisions.

B.9 Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)] [326 IAC 2-7-5(3)(C)]

- (a) Where specifically designated by this permit or required by an applicable requirement, any application form, report, or compliance certification submitted shall contain certification by a responsible official of truth, accuracy, and completeness. This certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- (b) One (1) certification shall be included, using the attached Certification Form, with each submittal requiring certification.
- (c) A responsible official is defined at 326 IAC 2-7-1(34).

B.10 Annual Compliance Certification [326 IAC 2-7-6(5)]

(a) The Permittee shall annually submit a compliance certification report which addresses the status of the source's compliance with the terms and conditions contained in this permit, including emission limitations, standards, or work practices. All certifications shall cover the time period from January 1 to December 31 of the previous year, and shall be submitted in letter form no later than July 1 of each year to:

Indiana Department of Environmental Management Compliance Branch, Office of Air Quality 100 North Senate Avenue, P. O. Box 6015 Indianapolis, Indiana 46206-6015

and

United States Environmental Protection Agency, Region V Air and Radiation Division, Air Enforcement Branch - Indiana (AE-17J) 77 West Jackson Boulevard Chicago, Illinois 60604-3590

(b) The annual compliance certification report required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on

or before the date it is due.

- (c) The annual compliance certification report shall include the following:
 - (1) The appropriate identification of each term or condition of this permit that is the basis of the certification:
 - (2) The compliance status;
 - (3) Whether compliance was continuous or intermittent;
 - (4) The methods used for determining the compliance status of the source, currently and over the reporting period consistent with 326 IAC 2-7-5(3); and
 - (5) Such other facts, as specified in Sections D of this permit, as IDEM, OAQ may require to determine the compliance status of the source.

The submittal by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

B.11 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)] [326 IAC 2-7-6(1) and (6)] [326 IAC 1-6-3]

- (a) If required by specific condition(s) in Section D of this permit, the Permittee shall maintain and implement Preventive Maintenance Plans (PMPs) including the following information on each facility:
 - (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
 - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and
 - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.
- (b) The Permittee shall implement the PMPs as necessary to ensure that failure to implement a PMP does not cause or contribute to a violation of any limitation on emissions or potential to emit.
- (c) A copy of the PMPs shall be submitted to IDEM, OAQ upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ. IDEM, OAQ may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or contributes to any violation. The PMP does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (d) Records of preventive maintenance shall be retained for a period of at least five (5) years. These records shall be kept at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.

B.12 Emergency Provisions [326 IAC 2-7-16]

(a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation.

Masonite Door Corporation Page 9 of 31 Richmond, Indiana T177-16192-00068

Permit Reviewer: Jed D. Wolkins

(b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describe the following:

- (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;
- (2) The permitted facility was at the time being properly operated;
- During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;
- (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAQ within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

Telephone Number: 1-800-451-6027 (ask for Office of Air Quality, Compliance

Section), or

Telephone Number: 317-233-5674 (ask for Compliance Section)

Facsimile Number: 317-233-5967

(5) For each emergency lasting one (1) hour or more, the Permittee submitted the attached Emergency Occurrence Report Form or its equivalent, either by mail or facsimile to:

Indiana Department of Environmental Management Compliance Branch, Office of Air Quality 100 North Senate Avenue, P. O. Box 6015 Indianapolis, Indiana 46206-6015

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-7-5(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;
- (B) Any steps taken to mitigate the emissions; and
- (C) Corrective actions taken.

The notification which shall be submitted by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (6) The Permittee immediately took all reasonable steps to correct the emergency.
- (c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.
- (d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions). This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.

- (e) IDEM, OAQ may require that the Preventive Maintenance Plans required under 326 IAC 2-7-4(c)(9) be revised in response to an emergency.
- (f) Failure to notify IDEM, OAQ by telephone or facsimile of an emergency lasting more than one (1) hour in accordance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-7 and any other applicable rules.
- (g) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.
- (h) The Permittee shall include all emergencies in the Quarterly Deviation and Compliance Monitoring Report.

B.13 Permit Shield [326 IAC 2-7-15] [326 IAC 2-7-20] [326 IAC 2-7-12]

(a) Pursuant to 326 IAC 2-7-15, the Permittee has been granted a permit shield. The permit shield provides that compliance with the conditions of this permit shall be deemed in compliance with any applicable requirements as of the date of permit issuance, provided that either the applicable requirements are included and specifically identified in this permit or the permit contains an explicit determination or concise summary of a determination that other specifically identified requirements are not applicable. The Indiana statutes from IC 13 and rules from 326 IAC, referenced in conditions in this permit, are those applicable at the time the permit was issued. The issuance or possession of this permit shall not alone constitute a defense against an alleged violation of any law, regulation or standard, except for the requirement to obtain a Part 70 permit under 326 IAC 2-7 or for applicable requirements for which a permit shield has been granted.

This permit shield does not extend to applicable requirements which are promulgated after the date of issuance of this permit unless this permit has been modified to reflect such new requirements.

- (b) If, after issuance of this permit, it is determined that the permit is in nonconformance with an applicable requirement that applied to the source on the date of permit issuance, IDEM, OAQ shall immediately take steps to reopen and revise this permit and issue a compliance order to the Permittee to ensure expeditious compliance with the applicable requirement until the permit is reissued. The permit shield shall continue in effect so long as the Permittee is in compliance with the compliance order.
- (c) No permit shield shall apply to any permit term or condition that is determined after issuance of this permit to have been based on erroneous information supplied in the permit application. Erroneous information means information that the Permittee knew to be false, or in the exercise of reasonable care should have been known to be false, at the time the information was submitted.
- (d) Nothing in 326 IAC 2-7-15 or in this permit shall alter or affect the following:
 - (1) The provisions of Section 303 of the Clean Air Act (emergency orders), including the authority of the U.S. EPA under Section 303 of the Clean Air Act;
 - (2) The liability of the Permittee for any violation of applicable requirements prior to or at the time of this permit's issuance;
 - (3) The applicable requirements of the acid rain program, consistent with Section

408(a) of the Clean Air Act; and

- (4) The ability of U.S. EPA to obtain information from the Permittee under Section 114 of the Clean Air Act.
- (f) This permit shield is not applicable to any change made under 326 IAC 2-7-20(b)(2) (Sections 502(b)(10) of the Clean Air Act changes) and 326 IAC 2-7-20(c)(2) (trading based on State Implementation Plan (SIP) provisions).
- (g) This permit shield is not applicable to modifications eligible for group processing until after IDEM, OAQ, has issued the modifications. [326 IAC 2-7-12(c)(7)]
- (h) This permit shield is not applicable to minor Part 70 permit modifications until after IDEM, OAQ, has issued the modification. [326 IAC 2-7-12(b)(8)]

B.14 Prior Permits Superseded [326 IAC 2-1.1-9.5]

- (a) All terms and conditions of previous permits issued pursuant to permitting programs approved into the state implementation plan have been either
 - (1) incorporated as originally stated,
 - (2) revised, or
 - (3) deleted

by this permit.

(b) All previous registrations and permits are superseded by this permit.

B.15 Deviations from Permit Requirements and Conditions [326 IAC 2-7-5(3)(C)(ii)]

(a) Deviations from any permit requirements (for emergencies see Section B - Emergency Provisions), the probable cause of such deviations, and any response steps or preventive measures taken shall be reported to:

Indiana Department of Environmental Management Compliance Data Section, Office of Air Quality 100 North Senate Avenue, P.O. Box 6015 Indianapolis, Indiana 46206-6015

using the attached Quarterly Deviation and Compliance Monitoring Report, or its equivalent. A deviation required to be reported pursuant to an applicable requirement that exists independent of this permit, shall be reported according to the schedule stated in the applicable requirement and does not need to be included in this report.

The Quarterly Deviation and Compliance Monitoring Report does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

(b) A deviation is an exceedance of a permit limitation or a failure to comply with a requirement of the permit.

B.16 Permit Modification, Reopening, Revocation and Reissuance, or Termination [326 IAC 2-7-5(6)(C)] [326 IAC 2-7-8(a)] [326 IAC 2-7-9]

(a) This permit may be modified, reopened, revoked and reissued, or terminated for cause. The filing of a request by the Permittee for a Part 70 permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated

noncompliance does not stay any condition of this permit. [326 IAC 2-7-5(6)(C)] The notification by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) This permit shall be reopened and revised under any of the circumstances listed in IC 13-15-7-2 or if IDEM, OAQ determines any of the following:
 - (1) That this permit contains a material mistake.
 - (2) That inaccurate statements were made in establishing the emissions standards or other terms or conditions.
 - (3) That this permit must be revised or revoked to assure compliance with an applicable requirement. [326 IAC 2-7-9(a)(3)]
- (c) Proceedings by IDEM, OAQ to reopen and revise this permit shall follow the same procedures as apply to initial permit issuance and shall affect only those parts of this permit for which cause to reopen exists. Such reopening and revision shall be made as expeditiously as practicable. [326 IAC 2-7-9(b)]
- (d) The reopening and revision of this permit, under 326 IAC 2-7-9(a), shall not be initiated before notice of such intent is provided to the Permittee by IDEM, OAQ, at least thirty (30) days in advance of the date this permit is to be reopened, except that IDEM, OAQ may provide a shorter time period in the case of an emergency. [326 IAC 2-7-9(c)]

B.17 Permit Renewal [326 IAC 2-7-4]

(a) The application for renewal shall be submitted using the application form or forms prescribed by IDEM, OAQ and shall include the information specified in 326 IAC 2-7-4. Such information shall be included in the application for each emission unit at this source, except those emission units included on the trivial or insignificant activities list contained in 326 IAC 2-7-1(21) and 326 IAC 2-7-1(40). The renewal application does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Request for renewal shall be submitted to:

Indiana Department of Environmental Management Permits Branch, Office of Air Quality 100 North Senate Avenue, P.O. Box 6015 Indianapolis, Indiana 46206-6015

- (b) Timely Submittal of Permit Renewal [326 IAC 2-7-4(a)(1)(D)]
 - (1) A timely renewal application is one that is:
 - (A) Submitted at least nine (9) months prior to the date of the expiration of this permit; and
 - (B) If the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
 - (2) If IDEM, OAQ, upon receiving a timely and complete permit application, fails to

Masonite Door Corporation Richmond, Indiana Permit Reviewer: Jed D. Wolkins

issue or deny the permit renewal prior to the expiration date of this permit, this existing permit shall not expire and all terms and conditions shall continue in effect, including any permit shield provided in 326 IAC 2-7-15, until the renewal permit has been issued or denied.

- (c) Right to Operate After Application for Renewal [326 IAC 2-7-3] If the Permittee submits a timely and complete application for renewal of this permit, the source's failure to have a permit is not a violation of 326 IAC 2-7 until IDEM, OAQ takes final action on the renewal application, except that this protection shall cease to apply if, subsequent to the completeness determination, the Permittee fails to submit by the deadline specified in writing by IDEM, OAQ any additional information identified as being needed to process the application.
- (d) United States Environmental Protection Agency Authority [326 IAC 2-7-8(e)] If IDEM, OAQ fails to act in a timely way on a Part 70 permit renewal, the U.S. EPA may invoke its authority under Section 505(e) of the Clean Air Act to terminate or revoke and reissue a Part 70 permit.

B.18 Permit Amendment or Modification [326 IAC 2-7-11] [326 IAC 2-7-12]

- (a) Permit amendments and modifications are governed by the requirements of 326 IAC 2-7-11 or 326 IAC 2-7-12 whenever the Permittee seeks to amend or modify this permit.
- (b) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management Permits Branch, Office of Air Quality 100 North Senate Avenue, P.O. Box 6015 Indianapolis, Indiana 46206-6015

Any such application shall be certified by the "responsible official" as defined by 326 IAC 2-7-1(34).

(c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

B.19 Permit Revision Under Economic Incentives and Other Programs [326 IAC 2-7-5(8)] [326 IAC 2-7-12 (b)(2)]

- (a) No Part 70 permit revision shall be required under any approved economic incentives, marketable Part 70 permits, emissions trading, and other similar programs or processes for changes that are provided for in a Part 70 permit.
- (b) Notwithstanding 326 IAC 2-7-12(b)(1) and 326 IAC 2-7-12(c)(1), minor Part 70 permit modification procedures may be used for Part 70 modifications involving the use of economic incentives, marketable Part 70 permits, emissions trading, and other similar approaches to the extent that such minor Part 70 permit modification procedures are explicitly provided for in the applicable State Implementation Plan (SIP) or in applicable requirements promulgated or approved by the U.S. EPA.

B.20 Operational Flexibility [326 IAC 2-7-20] [326 IAC 2-7-10.5]

(a) The Permittee may make any change or changes at the source that are described in 326 IAC 2-7-20(b), (c), or (e), without a prior permit revision, if each of the following conditions is met:

Masonite Door Corporation Page 14 of 31 Richmond, Indiana T177-16192-00068

Permit Reviewer: Jed D. Wolkins

(1) The changes are not modifications under any provision of Title I of the Clean Air Act;

- (2) Any preconstruction approval required by 326 IAC 2-7-10.5 has been obtained;
- (3) The changes do not result in emissions which exceed the emissions allowable under this permit (whether expressed herein as a rate of emissions or in terms of total emissions);
- (4) The Permittee notifies the:

Indiana Department of Environmental Management Permits Branch, Office of Air Quality 100 North Senate Avenue, P. O. Box 6015 Indianapolis, Indiana 46206-6015

and

United States Environmental Protection Agency, Region V Air and Radiation Division, Regulation Development Branch - Indiana (AR-18J) 77 West Jackson Boulevard Chicago, Illinois 60604-3590

in advance of the change by written notification at least ten (10) days in advance of the proposed change. The Permittee shall attach every such notice to the Permittee's copy of this permit; and

(5) The Permittee maintains records on-site which document, on a rolling five (5) year basis, all such changes and emissions trading that are subject to 326 IAC 2-7-20(b), (c), or (e) and makes such records available, upon reasonable request, for public review.

Such records shall consist of all information required to be submitted to IDEM, OAQ in the notices specified in 326 IAC 2-7-20(b)(1), (c)(1), and (e)(2).

- (b) The Permittee may make Section 502(b)(10) of the Clean Air Act changes (this term is defined at 326 IAC 2-7-1(36)) without a permit revision, subject to the constraint of 326 IAC 2-7-20(a). For each such Section 502(b)(10) of the Clean Air Act change, the required written notification shall include the following:
 - (1) A brief description of the change within the source;
 - (2) The date on which the change will occur;
 - (3) Any change in emissions; and
 - (4) Any permit term or condition that is no longer applicable as a result of the change.

The notification which shall be submitted is not considered an application form, report or compliance certification. Therefore, the notification by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

(c) Emission Trades [326 IAC 2-7-20(c)]

The Permittee may trade increases and decreases in emissions in the source, where the applicable SIP provides for such emission trades without requiring a permit revision,

Permit Reviewer: Jed D. Wolkins

subject to the constraints of Section (a) of this condition and those in 326 IAC 2-7-20(c).

(d) Alternative Operating Scenarios [326 IAC 2-7-20(d)]

The Permittee may make changes at the source within the range of alternative operating scenarios that are described in the terms and conditions of this permit in accordance with 326 IAC 2-7-5(9). No prior notification of IDEM, OAQ, or U.S. EPA is required.

B.21 Source Modification Requirement [326 IAC 2-7-10.5]

A modification, construction, or reconstruction is governed by the requirements of 326 IAC 2 and 326 IAC 2-7-10.5.

B.22 Inspection and Entry [326 IAC 2-7-6] [IC 13-14-2-2]

Upon presentation of proper identification cards, credentials, and other documents as may be required by law, and subject to the Permittee's right under all applicable laws and regulations to assert that the information collected by the agency is confidential and entitled to be treated as such, the Permittee shall allow IDEM, OAQ, U.S. EPA, or an authorized representative to perform the following:

- (a) Enter upon the Permittee's premises where a Part 70 source is located, or emissions related activity is conducted, or where records must be kept under the conditions of this permit;
- (b) Have access to and copy any records that must be kept under the conditions of this permit;
- (c) Inspect any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit;
- (d) Sample or monitor substances or parameters for the purpose of assuring compliance with this permit or applicable requirements; and
- (e) Utilize any photographic, recording, testing, monitoring, or other equipment for the purpose of assuring compliance with this permit or applicable requirements.

B.23 Transfer of Ownership or Operational Control [326 IAC 2-7-11]

- (a) The Permittee must comply with the requirements of 326 IAC 2-7-11 whenever the Permittee seeks to change the ownership or operational control of the source and no other change in the permit is necessary.
- (b) Any application requesting a change in the ownership or operational control of the source shall contain a written agreement containing a specific date for transfer of permit responsibility, coverage and liability between the current and new Permittee. The application shall be submitted to:

Indiana Department of Environmental Management Permits Branch, Office of Air Quality 100 North Senate Avenue, P.O. Box 6015 Indianapolis, Indiana 46206-6015

The application which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

(c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326]

IAC 2-7-11(c)(3)]

B.24 Annual Fee Payment [326 IAC 2-7-19] [326 IAC 2-7-5(7)][326 IAC 2-1.1-7]

- (a) The Permittee shall pay annual fees to IDEM, OAQ within thirty (30) calendar days of receipt of a billing. Pursuant to 326 IAC 2-7-19(b), if the Permittee does not receive a bill from IDEM, OAQ, the applicable fee is due April 1 of each year.
- (b) Except as provided in 326 IAC 2-7-19(e), failure to pay may result in administrative enforcement action or revocation of this permit.
- (c) The Permittee may call the following telephone numbers: 1-800-451-6027 or 317-233-4230 (ask for OAQ, I/M & Billing Section), to determine the appropriate permit fee.

SECTION C

SOURCE OPERATION CONDITIONS

Entire Source

Emission Limitations and Standards [326 IAC 2-7-5(1)]

- C.1 Particulate Emission Limitations For Processes with Process Weight Rates Less Than One Hundred (100) pounds per hour [40 CFR 52 Subpart P][326 IAC 6-3-2]
 - (a) Pursuant to 40 CFR 52 Subpart P, the allowable particulate matter emissions rate from any process not already regulated by 326 IAC 6-1 or any New Source Performance Standard, and which has a maximum process weight rate less than 100 pounds per hour shall not exceed 0.551 pounds per hour.
 - (b) Pursuant to 326 IAC 6-3-2(e)(2), the allowable particulate emissions rate from any process not exempt under 326 IAC 6-3-1(b) or (c) which has a maximum process weight rate less than 100 pounds per hour and the methods in 326 IAC 6-3-2(b) through (d) do not apply shall not exceed 0.551 pounds per hour. This condition is not federally enforceable.

C.2 Opacity [326 IAC 5-1]

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

C.3 Open Burning [326 IAC 4-1] [IC 13-17-9]

The Permittee shall not open burn any material except as provided in 326 IAC 4-1-3, 326 IAC 4-1-4 or 326 IAC 4-1-6. The previous sentence notwithstanding, the Permittee may open burn in accordance with an open burning approval issued by the Commissioner under 326 IAC 4-1-4.1. 326 IAC 4-1-3 (a)(2)(A) and (B) are not federally enforceable.

C.4 Incineration [326 IAC 4-2] [326 IAC 9-1-2]

The Permittee shall not operate an incinerator or incinerate any waste or refuse except as provided in 326 IAC 4-2 and 326 IAC 9-1-2.

C.5 Fugitive Dust Emissions [326 IAC 6-4]

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions). 326 IAC 6-4-2(4) is not federally enforceable.

C.6 Operation of Equipment [326 IAC 2-7-6(6)]

Except as otherwise provided by statute or rule, or in this permit, all air pollution control equipment listed in this permit and used to comply with an applicable requirement shall be operated at all times that the emission units vented to the control equipment are in operation.

C.7 Asbestos Abatement Projects [326 IAC 14-10] [326 IAC 18] [40 CFR 61, Subpart M]

(a) Notification requirements apply to each owner or operator. If the combined amount of regulated asbestos containing material (RACM) to be stripped, removed or disturbed is at

least 260 linear feet on pipes or 160 square feet on other facility components, or at least thirty-five (35) cubic feet on all facility components, then the notification requirements of 326 IAC 14-10-3 are mandatory. All demolition projects require notification whether or not asbestos is present.

- (b) The Permittee shall ensure that a written notification is sent on a form provided by the Commissioner at least ten (10) working days before asbestos stripping or removal work or before demolition begins, per 326 IAC 14-10-3, and shall update such notice as necessary, including, but not limited to the following:
 - (1) When the amount of affected asbestos containing material increases or decreases by at least twenty percent (20%); or
 - (2) If there is a change in the following:
 - (A) Asbestos removal or demolition start date;
 - (B) Removal or demolition contractor; or
 - (C) Waste disposal site.
- (c) The Permittee shall ensure that the notice is postmarked or delivered according to the guidelines set forth in 326 IAC 14-10-3(2).
- (d) The notice to be submitted shall include the information enumerated in 326 IAC 14-10-3(3).

All required notifications shall be submitted to:

Indiana Department of Environmental Management Asbestos Section, Office of Air Quality 100 North Senate Avenue, P.O. Box 6015 Indianapolis, Indiana 46206-6015

The notice shall include a signed certification from the owner or operator that the information provided in this notification is correct and that only Indiana licensed workers and project supervisors will be used to implement the asbestos removal project. The notifications do not require a certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (e) Procedures for Asbestos Emission Control
 The Permittee shall comply with the applicable emission control procedures in 326 IAC 1410-4 and 40 CFR 61.145(c). Per 326 IAC 14-10-1, emission control requirements are
 applicable for any removal or disturbance of RACM greater than three (3) linear feet on
 pipes or three (3) square feet on any other facility components or a total of at least 0.75
 cubic feet on all facility components.
- (f) Indiana Accredited Asbestos Inspector
 The Permittee shall comply with 326 IAC 14-10-1(a) that requires the owner or operator,
 prior to a renovation/demolition, to use an Indiana Accredited Asbestos Inspector to
 thoroughly inspect the affected portion of the facility for the presence of asbestos. The
 requirement that the inspector be accredited, pursuant to the provisions of 40 CFR 61,
 Subpart M, is federally enforceable.

C.8 Performance Testing [326 IAC 3-6]

(a) All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this permit, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAQ.

A test protocol, except as provided elsewhere in this permit, shall be submitted to:

Indiana Department of Environmental Management Compliance Data Section, Office of Air Quality 100 North Senate Avenue, P. O. Box 6015 Indianapolis, Indiana 46206-6015

no later than thirty-five (35) days prior to the intended test date. The protocol submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) The Permittee shall notify IDEM, OAQ of the actual test date at least fourteen (14) days prior to the actual test date. The notification submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ not later than forty-five (45) days after the completion of the testing. An extension may be granted by IDEM, OAQ, if the source submits to IDEM, OAQ a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.

Compliance Requirements [326 IAC 2-1.1-11]

C.9 Compliance Requirements [326 IAC 2-1.1-11]

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements by issuing an order under 326 IAC 2-1.1-11. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U. S. EPA.

Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]

C.10 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]

Unless otherwise specified in this permit, all monitoring and record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance. If required by Section D, the Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment. If due to circumstances beyond its control, that equipment cannot be installed and operated within ninety (90) days, the Permittee may extend the compliance schedule related to the equipment for an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management Compliance Branch, Office of Air Quality 100 North Senate Avenue, P. O. Box 6015 Indianapolis, Indiana 46206-6015

in writing, prior to the end of the initial ninety (90) day compliance schedule, with full justification of the reasons for the inability to meet this date.

The notification which shall be submitted by the Permittee does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Masonite Door Corporation Richmond, Indiana Permit Reviewer: Jed D. Wolkins

> Unless otherwise specified in the approval for the new emission unit(s), compliance monitoring for new emission units or emission units added through a source modification shall be implemented when operation begins.

C.11 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]

Any monitoring or testing required by Section D of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, 40 CFR 60 Appendix B, 40 CFR 63, or other approved methods as specified in this permit.

Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]

C.12 Emergency Reduction Plans [326 IAC 1-5-2] [326 IAC 1-5-3]

Pursuant to 326 IAC 1-5-2 (Emergency Reduction Plans; Submission):

- (a) The Permittee prepared and submitted written emergency reduction plans (ERPs) consistent with safe operating procedures on 3/10/03.
- (b) Upon direct notification by IDEM, OAQ, that a specific air pollution episode level is in effect, the Permittee shall immediately put into effect the actions stipulated in the approved ERP for the appropriate episode level.
 [326 IAC 1-5-3]

C.13 Risk Management Plan [326 IAC 2-7-5(12)] [40 CFR 68.215]

If a regulated substance, subject to 40 CFR 68, is present at a source in more than a threshold quantity, 40 CFR 68 is an applicable requirement and the Permittee shall submit:

- (a) A compliance schedule for meeting the requirements of 40 CFR 68; or
- (b) As a part of the annual compliance certification submitted under 326 IAC 2-7-6(5), a certification statement that the source is in compliance with all the requirements of 40 CFR 68, including the registration and submission of a Risk Management Plan (RMP).

All documents submitted pursuant to this condition shall include the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

C.14 Compliance Response Plan - Preparation, Implementation, Records, and Reports [326 IAC 2-7-5] [326 IAC 2-7-6]

- (a) The Permittee is required to prepare a Compliance Response Plan (CRP) for each compliance monitoring condition of this permit. A CRP shall be submitted to IDEM, OAQ upon request. The CRP shall be prepared within ninety (90) days after issuance of this permit by the Permittee, supplemented from time to time by the Permittee, maintained on site, and comprised of:
 - (1) Reasonable response steps that may be implemented in the event that a response step is needed pursuant to the requirements of Section D of this permit; and an expected timeframe for taking reasonable response steps.
 - (2) If, at any time, the Permittee takes reasonable response steps that are not set forth in the Permittee's current Compliance Response Plan and the Permittee documents such response in accordance with subsection (e) below, the Permittee shall amend its Compliance Response Plan to include such response steps taken.
- (b) For each compliance monitoring condition of this permit, reasonable response steps shall

Masonite Door Corporation Page 21 of 31 Richmond, Indiana T177-16192-00068

Permit Reviewer: Jed D. Wolkins

be taken when indicated by the provisions of that compliance monitoring condition as follows:

- (1) Reasonable response steps shall be taken as set forth in the Permittee's current Compliance Response Plan; or
- (2) If none of the reasonable response steps listed in the Compliance Response Plan is applicable or responsive to the excursion, the Permittee shall devise and implement additional response steps as expeditiously as practical. Taking such additional response steps shall not be considered a deviation from this permit so long as the Permittee documents such response steps in accordance with this condition.
- (3) If the Permittee determines that additional response steps would necessitate that the emissions unit or control device be shut down, the IDEM, OAQ shall be promptly notified of the expected date of the shut down, the status of the applicable compliance monitoring parameter with respect to normal, and the results of the actions taken up to the time of notification.
- (4) Failure to take reasonable response steps shall constitute a violation of the permit.
- (c) The Permittee is not required to take any further response steps for any of the following reasons:
 - (1) A false reading occurs due to the malfunction of the monitoring equipment and prompt action was taken to correct the monitoring equipment.
 - (2) The Permittee has determined that the compliance monitoring parameters established in the permit conditions are technically inappropriate, has previously submitted a request for a minor permit modification to the permit, and such request has not been denied.
 - (3) An automatic measurement was taken when the process was not operating.
 - (4) The process has already returned or is returning to operating within "normal" parameters and no response steps are required.
- (d) When implementing reasonable steps in response to a compliance monitoring condition, if the Permittee determines that an exceedance of an emission limitation has occurred, the Permittee shall report such deviations pursuant to Section B-Deviations from Permit Requirements and Conditions.
- (e) The Permittee shall record all instances when response steps are taken. In the event of an emergency, the provisions of 326 IAC 2-7-16 (Emergency Provisions) requiring prompt corrective action to mitigate emissions shall prevail.
- (f) Except as otherwise provided by a rule or provided specifically in Section D, all monitoring as required in Section D shall be performed when the emission unit is operating, except for time necessary to perform quality assurance and maintenance activities.
- C.15 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5] [326 IAC 2-7-6]
 - (a) When the results of a stack test performed in conformance with Section C Performance Testing, of this permit exceed the level specified in any condition of this permit, the Permittee shall take appropriate response actions. The Permittee shall submit a

description of these response actions to IDEM, OAQ, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize excess emissions from the affected facility while the response actions are being implemented.

- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAQ that retesting in one-hundred and twenty (120) days is not practicable, IDEM, OAQ may extend the retesting deadline.
- (c) IDEM, OAQ reserves the authority to take any actions allowed under law in response to noncompliant stack tests.

The documents submitted pursuant to this condition do require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

- C.16 Emission Statement [326 IAC 2-7-5(3)(C)(iii)] [326 IAC 2-7-5(7)] [326 IAC 2-7-19(c)] [326 IAC 2-6]
 - (a) The Permittee shall submit an annual emission statement certified pursuant to the requirements of 326 IAC 2-6, that must be received by July 1 of each year and must comply with the minimum requirements specified in 326 IAC 2-6-4. The annual emission statement shall meet the following requirements:
 - (1) Indicate estimated actual emissions of criteria pollutants from the source, in compliance with 326 IAC 2-6 (Emission Reporting);
 - (2) Indicate estimated actual emissions of other regulated pollutants (as defined by 326 IAC 2-7-1) from the source, for purposes of Part 70 fee assessment.
 - (b) The annual emission statement covers the twelve (12) consecutive month time period starting January 1 and ending December 31. The annual emission statement must be submitted to:

Indiana Department of Environmental Management Technical Support and Modeling Section, Office of Air Quality 100 North Senate Avenue, P. O. Box 6015 Indianapolis, Indiana 46206-6015

The emission statement does require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

(c) The annual emission statement required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.

C.17 General Record Keeping Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-6]

(a) Records of all required data, reports, and support information shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be kept at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable

time.

(b) Unless otherwise specified in this permit, all record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.

C.18 General Reporting Requirements [326 IAC 2-7-5(3)(C)] [326 IAC 2-1.1-11]

- (a) The source shall submit the attached Quarterly Deviation and Compliance Monitoring Report or its equivalent. Any deviation from permit requirements, the date(s) of each deviation, the cause of the deviation, and the response steps taken must be reported. This report shall be submitted within thirty (30) days of the end of the reporting period. The Quarterly Deviation and Compliance Monitoring Report shall include the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (b) The report required in (a) of this condition and reports required by conditions in Section D of this permit shall be submitted to:

Indiana Department of Environmental Management Compliance Data Section, Office of Air Quality 100 North Senate Avenue, P. O. Box 6015 Indianapolis, Indiana 46206-6015

- (c) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ on or before the date it is due.
- (d) Unless otherwise specified in this permit, all reports required in Section D of this permit shall be submitted within thirty (30) days of the end of the reporting period. All reports do require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (e) Reporting periods are based on calendar years.

Stratospheric Ozone Protection

C.19 Compliance with 40 CFR 82 and 326 IAC 22-1

Pursuant to 40 CFR 82 (Protection of Stratospheric Ozone), Subpart F, except as provided for motor vehicle air conditioners in Subpart B, the Permittee shall comply with the standards for recycling and emissions reduction:

- (a) Persons opening appliances for maintenance, service, repair, or disposal must comply with the required practices pursuant to 40 CFR 82.156.
- (b) Equipment used during the maintenance, service, repair, or disposal of appliances must comply with the standards for recycling and recovery equipment pursuant to 40 CFR 82.158.
- (c) Persons performing maintenance, service, repair, or disposal of appliances must be certified by an approved technician certification program pursuant to 40 CFR 82.161.

Part 2 MACT Application Submittal Requirement

63.56(a)] [40 CFR 63.9(b)] [326 IAC 2-7-12]

- (a) The Permittee shall submit a Part 2 MACT Application in accordance with 40 CFR 63.52(e)(1). The Part 2 MACT Application shall meet the requirements of 40 CFR 63.53(b).
- (b) Notwithstanding paragraph (a), the Permittee is not required to submit a Part 2 MACT Application if the Permittee no longer meets the applicability criteria of 40 CFR 63.50 by the application deadline in 40 CFR 63.52(e)(1). For example, the Permittee would not have to submit a Part 2 MACT Application if, by the application deadline:
 - (1) The source is no longer a major source of hazardous air pollutants, as defined in 40 CFR 63.2;
 - (2) The source no longer includes one or more units in an affected source category for which the U.S. EPA failed to promulgate an emission standard by May 15, 2002; or
 - (3) The MACT standard or standards for the affected source categories included at the source are promulgated.
- (c) Notwithstanding paragraph (a), pursuant to 40 CFR 63.56(a), the Permittee shall comply with an applicable promulgated MACT standard in accordance with the schedule provided in the MACT standard if the MACT standard is promulgated prior to the Part 2 MACT Application deadline or prior to the issuance of permit with a case-by-case Section 112(j) MACT determination. The MACT requirements include the applicable General Provisions requirements of 40 CFR 63, Subpart A. Pursuant to 40 CFR 63.9(b), the Permittee shall submit an initial notification not later than 120 days after the effective date of the MACT, unless the MACT specifies otherwise. The initial notification shall be submitted to:

Indiana Department of Environmental Management Compliance Data Section, Office of Air Quality 100 North Senate Avenue, P.O. Box 6015 Indianapolis, Indiana 46206-6015

and

United States Environmental Protection Agency, Region V Director, Air and Radiation Division 77 West Jackson Boulevard Chicago, Illinois 60604-3590 Masonite Door Corporation Richmond, Indiana Permit Reviewer: Jed D. Wolkins

SECTION D.1

FACILITY OPERATION CONDITIONS

Facility Description [326 IAC 2-7-5(15)]:

Two (2) surface coating silos, identified as Paint 1 and Paint 2, both constructed after July 1977 and before January 1980, each with a maximum capacity of 12 feet of door per minute, both utilizing the electrostatic disc method of paint application, both connected to an auxiliary natural gas oven, both using dry filters as control, and exhausting to vents C1 and C2, respectively.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

Emission Limitations and Standards [326 IAC 2-7-5(1)]

D.1.1 Volatile Organic Compounds (VOC) [326 IAC 8-6]

Any change or modification which will start the use of any solvent not exempted in 326 IAC 8-6-2 (4) at the source must be approved by the Office of Air Quality (OAQ) before such change may occur.

D.1.2 Particulate Matter (PM) [40 CFR 52 Subpart P]

Pursuant to T-177–7479-00068, issued on 9/28/1998 and 40 CFR 52 Subpart P, the PM from the two (2) surface coating silos (Paint 1 and Paint 2) shall not exceed the pound per hour emission rate established as E in the following formula:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

 $E = 4.10 P^{0.67}$ where E = rate of emission in pounds per hour; and P = process weight rate in tons per hour

D.1.3 Particulate [326 IAC 6-3-2(d)]

Pursuant to 326 IAC 6-3-2(d), particulate from the two (2) surface coating silos (Paint 1 and Paint 2) shall be controlled by the dry particulate filters, and the Permittee shall operate the control devices in accordance with manufacturer's specifications. This requirement to operate the control is not federally enforceable.

D.1.4 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section B - Preventive Maintenance Plan, of this permit, is required for this facility and any control devices.

Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]

D.1.5 Monitoring

(a) Daily inspections shall be performed to verify the placement, integrity and particle loading of the filters. To monitor the performance of the dry filters, weekly observations shall be made of the overspray from the surface coating silo vents C1 and C2 while one or more of the silos are in operation. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C.14 - Compliance Response Plan - Preparation, Implementation,

Records, and Reports, shall be considered a violation of this permit.

- (b) Monthly inspections shall be performed of the coating emissions from the vents C1 and C2 and the presence of overspray on the rooftops and the nearby ground. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when a noticeable change in overspray emission, or evidence of overspray emission is observed. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C.14 Compliance Response Plan Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.
- (c) Additional inspections and preventive measures shall be performed as prescribed in the Preventive Maintenance Plan.

Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]

D.1.6 Record Keeping Requirements

- (a) To document compliance with Conditions D.1.1, the Permittee shall maintain records in accordance with (1) through (6) below. Records maintained for (1) through (6) shall be taken monthly and shall be complete and sufficient to establish compliance with the solvent usage limit established in Condition D.1.1.
 - (1) The VOC content of each coating material and solvent used.
 - (2) The amount of coating material and solvent less water used on a monthly basis.
 - (A) Records shall include purchase orders, invoices, and material safety data sheets (MSDS) necessary to verify the type and amount used.
 - (B) Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents.
 - (3) The volume weighted VOC content of the coatings used for each month;
 - (4) The cleanup solvent usage for each month;
 - (5) The total VOC usage for each month; and
 - (6) The weight of VOCs emitted for each compliance period.
- (b) To document compliance with Condition D.1.5, the Permittee shall maintain a log of weekly overspray observations, daily and monthly inspections, and those additional inspections prescribed by the Preventive Maintenance Plan.
- (c) All records shall be maintained in accordance with Section C.17 General Record Keeping Requirements, of this permit.

Masonite Door Corporation Richmond, Indiana Permit Reviewer: Jed D. Wolkins

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

PART 70 OPERATING PERMIT CERTIFICATION

OFFICE OF AIR QUALITY

Source Name: Masonite Door Corporation

Source Address: 305 Industrial Parkway, Richmond, Indiana 47374

Mailing Address: P.O. Box 667, Richmond, IN 47374

Part 70 Permit No.: T177-16192-00068				
This certification shall be included when submitting monitoring, testing reports/results or other documents as required by this permit.				
Please check what document is being certified:				
? Annual Compliance Certification Letter				
? Test Result (specify)				
? Report (specify)				
? Notification (specify)				
? Affidavit (specify)				
? Other (specify)				
	_			
I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.	1			
Signature:				
Printed Name:				
Title/Position:				
Phone:				
Date:				

Masonite Door Corporation Page 28 of 31
Richmond, Indiana T177-16192-00068
Permit Reviewer: Jed D. Wolkins

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

COMPLIANCE BRANCH 100 North Senate Avenue P.O. Box 6015 Indianapolis, Indiana 46206-6015 Phone: 317-233-5674 Fax: 317-233-5967

OFFICE OF AIR QUALITY

PART 70 OPERATING PERMIT EMERGENCY OCCURRENCE REPORT

Source Name: Masonite Door Corporation

Source Address: 305 Industrial Parkway, Richmond, Indiana 47374

Mailing Address: P.O. Box 667, Richmond, IN 47374

Part 70 Permit No.: T177-16192-00068

This form consists of 2 pages

Page 1 of 2

? This is an emergency as defined in 326 IAC 2-7-1(12)

- ? The Permittee must notify the Office of Air Quality (OAQ), within four (4) business hours (1-800-451-6027 or 317-233-5674, ask for Compliance Section); and
- ? The Permittee must submit notice in writing or by facsimile within two (2) working days (Facsimile Number: 317-233-5967), and follow the other requirements of 326 IAC 2-7-16.

If any of the following are not applicable, mark N/A

Facility/Equipment/Operation:
Control Family as out
Control Equipment:
Permit Condition or Operation Limitation in Permit:
Description of the Emergency:
Describe the cause of the Emergency:

If any of the following are not applicable, mark N/A Page 2 of 2 Date/Time Emergency started: Date/Time Emergency was corrected: Was the facility being properly operated at the time of the emergency? Υ Ν Describe: Type of Pollutants Emitted: TSP, PM-10, SO₂, VOC, NO_x, CO, Pb, other: Estimated amount of pollutant(s) emitted during emergency: Describe the steps taken to mitigate the problem: Describe the corrective actions/response steps taken: Describe the measures taken to minimize emissions: If applicable, describe the reasons why continued operation of the facilities are necessary to prevent imminent injury to persons, severe damage to equipment, substantial loss of capital investment, or loss of product or raw materials of substantial economic value:

Form Completed by:

Title / Position:

Date:

Phone:

A certification is not required for this report.

INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR QUALITY COMPLIANCE DATA SECTION

PART 70 OPERATING PERMIT QUARTERLY DEVIATION AND COMPLIANCE MONITORING REPORT

Source Name: Masonite Door Corporation Source Address: 305 Industrial Parkway, Richmond, Indiana 47374 P.O. Box 667, Richmond, IN 47374 Mailing Address: Part 70 Permit No.: T177-16192-00068 Months: to Year: Page 1 of 2 This report shall be submitted quarterly based on a calendar year. Any deviation from the requirements, the date(s) of each deviation, the probable cause of the deviation, and the response steps taken must be reported. Deviations that are required to be reported by an applicable requirement shall be reported according to the schedule stated in the applicable requirement and do not need to be included in this report. Additional pages may be attached if necessary. If no deviations occurred, please specify in the box marked "No deviations occurred this reporting period". ? NO DEVIATIONS OCCURRED THIS REPORTING PERIOD. ? THE FOLLOWING DEVIATIONS OCCURRED THIS REPORTING PERIOD Permit Requirement (specify permit condition #) Date of Deviation: **Duration of Deviation:** Number of Deviations: **Probable Cause of Deviation: Response Steps Taken: Permit Requirement** (specify permit condition #) Date of Deviation: **Duration of Deviation: Number of Deviations: Probable Cause of Deviation:** Response Steps Taken:

Page 2 of 2

Permit Requirement (specify permit condition #)		
Date of Deviation:	Duration of Deviation:	
Number of Deviations:		
Probable Cause of Deviation:		
Response Steps Taken:		
Permit Requirement (specify permit condition #)		
Date of Deviation:	Duration of Deviation:	
Number of Deviations:		
Probable Cause of Deviation:		
Response Steps Taken:		
Descrit Descripement (openity permit condition 4)		
Permit Requirement (specify permit condition #)	Denotion of Devictions	
Date of Deviation:	Duration of Deviation:	
Number of Deviations:		
Probable Cause of Deviation:		
Response Steps Taken:		
Form Completed By:		
Title/Position:		
Date:		
Phone:		

Attach a signed certification to complete this report.

Indiana Department of Environmental Management Office of Air Quality

Technical Support Document (TSD) for a Part 70 Operating Permit

Source Background and Description

Source Name: Masonite Door Corporation

Source Location: 305 Industrial Parkway, Richmond, Indiana 47374

County: Wayne SIC Code: 3442

Operation Permit No.: T177-16192-00068
Permit Reviewer: Jed D. Wolkins

The Office of Air Quality (OAQ) has reviewed a Part 70 permit application from Masonite Door Corporation relating to the operation of a metal door manufacturing plant.

Permitted Emission Units and Pollution Control Equipment

The source consists of the following permitted emission units and pollution control devices:

Two (2) surface coating silos, identified as Paint 1 and Paint 2, both constructed after July 1977 and before January 1980, each with a maximum capacity of 12 feet of door per minute, both utilizing the electrostatic disc method of paint application, both connected to an auxiliary natural gas oven, both using dry filters as control, and exhausting to vents C1 and C2, respectively.

Unpermitted Emission Units and Pollution Control Equipment

There are no unpermitted facilities operating at this source during this review process.

Insignificant Activities

The source also consists of the following insignificant activities, as defined in 326 IAC 2-7-1(21):

- (a) Space heaters, process heaters, or boilers using the following fuels:
 - (1) Natural gas-fired combustion sources with heat input equal to or less than ten million (10,000,000) Btu per hour.
- (b) Machining where an aqueous cutting coolant continuously floods the machining interface.
- (c) Any operation using aqueous solutions containing less than 1% by weight of VOCs, excluding HAPs.
- (d) Any operation using aqueous solutions containing less than 1% by weight of VOCs, excluding HAPs.

- (e) Mold release agents using low volatile products (vapor pressure less than or equal to 2 kilopascals measured at 38 degrees C).
- (f) Activities or categories of activities with individual HAP emissions not previously identified. (Door Foam Operations Methyl Diisocyanate)
- (g) Other activities or categories not previously identified below insignificant thresholds. (Door touch up area)

Existing Approvals

The source has been operating under previous approvals including, but not limited to, the following:

- (a) T 177-7479-00068 issued on 9-23-1998 and
- (b) AA 177-8712-00068 issued on 8-18-1997 and
- (c) AA 177-10405-00068 issued on 3-17-1999 and
- (d) AA 177-10683-00068 issued on 3-26-1999 and
- (e) RO 177-13530-00068 issued on 3-19-2002 and
- (b) AA 177-12983-00068 issued on 1-17-2001

All terms and conditions of previous permits issued pursuant to permitting programs approved into the state implementation plan have been either incorporated as originally stated, revised, or deleted by this permit. All previous registrations and permits are superseded by this permit.

The following terms and conditions from previous approvals have been revised in this Part 70 permit:(The **bold** language is new language that has been added, and the language with a line through it has been removed.)

(a) Condition D.1.1 Volatile Organic Compounds (VOC)
Anv change or modification which may increase the potential VOC emissions from the equipment covered in this permit will start the use of any solvent not exempted in 326 IAC 8-6-2 (4) at the source must be approved by the Office of Air ManagementQuality (OAMQ) before such change may occur.

Reason Chanded: The original limit was intended to allow IDEM check on the applicability of any rules if the PTE of VOCs above 100 tons per vear. The PTE of VOCs is 133 tons per vear. The only limit not previously identified is 326 IAC 8-6. The source does not currently use any solvents that are not exempt under 326 IAC 8-6-2 (4). Since many chandes allowed without permit action could add the use of a non-exempt solvent, IDEM, OAQ now requires the approval of any change adding a non-exempt solvent.

- (b) Condition D.1.6 Monitorina:
 - (a) Daily inspections shall be performed to verify the placement. integrity and particle loading of the filters. To monitor the performance of the dry filters, daily weekly observations shall be made of the overspray from the surface coating booth stacks silo vents C1 and C2 while one or more of the booths silos are in operation. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C Compliance Monitoring Plan Failure to Take Response Steps

Plan - Preparation. Implementation, Records, and Reports, shall be considered a violation of this permit.

- (b) Weekly Monthly inspections shall be performed of the coating emissions from the stack vents C1 and C2 and the presence of overspray on the rooftops and the nearby ground. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when a noticeable change in overspray emission, or evidence of overspray emission is observed. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C Compliance Monitoring Plan Failure to Take-Response Steps Plan Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.
- (c) Additional inspections and preventive measures shall be performed as prescribed in the Preventive Maintenance Plan.

Reason changed: Referenced units and condition have been renamed to match the rest permit. Daily observations of the overspray have been changed to weekly, and weekly inspections of coating emissions have been changed to monthly, as requested by the Permittee. The reduced frequency of the monitoring still meets the requirements to monitor per 326 IAC 2-7-5.

- (c) Condition D.1.7 Record Keepina Requirements:
 - (a) To document compliance with Conditions D.1.1, the Permittee shall maintain records in accordance with (1) through (56) below. Records maintained for (1) through (56) shall be taken monthly. These records and shall be complete and sufficient to establish compliance with the VOC solvent usage limits and/or the VOC emission limits limit established in Condition D.1.1.
 - (1) The amount and VOC content of each coating material and solvent used.
 - (2) The amount of coating material and solvent less water used on a monthly basis.
 - (A) Records shall include purchase orders. invoices. and material safety data sheets (MSDS) necessary to verify the type and amount used.
 - (B) Solvent usage records shall differentiate between those added to coatings and those used as cleanup solvents;.
 - (2) A log of the dates of use;
 - (3) The volume weighted VOC content of the coatings used for each month;
 - (4) The cleanup solvent usage for each month;
 - (45) The total VOC usage for each month; and
 - (56) The weight of VOCs emitted for each compliance period.
 - (b) To document compliance with Condition D.1.65, the Permittee shall maintain a log

Masonite Door Corporation Richmond, Indiana Permit Reviewer: Jed D. Wolkins

of dailvweeklv overspray observations. daily and weeklvmonthlv inspections, and those additional inspections prescribed by the Preventive Maintenance Plan.

(c) All records shall be maintained in accordance with Section C.17 - General Record Keeping Requirements, of this permit.

Reason revised: Record keeping for condition D.1.1 has updated to match the change in D.1.1. Daily observations of the overspray have been changed to weekly, and weekly inspections of coating emissions have been changed to monthly, to match condition D.1.5 Monitoring.

The following terms and conditions from previous approvals have been determined no longer applicable; therefore, were not incorporated into this Part 70 permit:

(a) Condition B.15 Multiple Exceedances:

Any exceedance of a permit limitation or condition contained in this permit, which occurs contemporaneously with an exceedance of an associated surrogate or operating parameter established to detect or assure compliance with that limit or condition, both arising out of the same act or occurrence, shall constitute a single potential violation of this permit.

Reason not incorporated: This condition has been removed because 326 IAC 2-7-5(1)(E) has been repealed, because it conflicted with 40 CFR 70.6(a)(6).

(b) Condition B.27 Enhanced New Source Review:

The requirements of the construction permit rules in 326 IAC 2 are satisfied by this permit for any previously unpermitted facilities and facilities to be constructed within eighteen (18) months after the date of issuance of this permit, as listed in Sections A.2 and A.3.

Reason not incorporated: This permit is just a Title V renewal. There are no unpermitted facilities or facilities to be constructed. The original Title V did need this condition as it was a construction permit.

(c) Condition B.28 Credible Evidence:

Not withstanding the conditions of this permit that state specific methods that may be used to assess compliance or noncompliance with applicable requirements, other credible evidence may be used to demonstrate compliance or non compliance.

Reason not incorporated: This condition is not necessary and has been removed from the permit. Indiana's statutes, and the rules adopted under their authority, govern the admissibility of evidence in any proceeding. Indiana law contains no provisions that limit the use of any credible evidence and an explicit statement is not required in the permit.

(d) Condition D.1.4 Testing Requirements:

The Permittee is not required to test this facility by this permit. However, IDEM may require compliance testing at any specific time when necessary to determine if the facility is in compliance. If testing is required by IDEM, compliance shall be determined by a performance test conducted in accordance with Section C - Performance Testing.

Reason not incorporated: Condition C.10 Compliance Requirements states the above condition for the entire source. Repeating the condition for this facility is unnecessary.

(e) Condition D.1.5 Particulate Matter (PM)

Pursuant to 326 IAC 6-3-2, the dry filters for PM control shall be in place at all times when the paint booths are in operation.

Reason not incorporated: 326 IAC 6-3 has been revised. The rule now requires particulate from the surface coating to be controlled by a dry particulate filter, waterwash, or an equivalent control device, and operated in accordance with manufacturer's specifications. The new section D.1.2 states this requirement.

(f) Section D.2: The entire section has been removed.

Reason not incorporated: The degreaser has been dismantled and removed from the source. The degreaser was the only unit listed in Section D.2.

Enforcement Issue

There are no enforcement actions pending.

Recommendation

The staff recommends to the Commissioner that the Part 70 permit be approved. This recommendation is based on the following facts and conditions:

Unless otherwise stated, information used in this review was derived from the application and additional information submitted by the applicant.

An administratively complete Part 70 permit application for the purposes of this review was received on 10/3/02. Additional information was received on 11/13/02, 12/2/02, 12/9/02, 12/10/02, 1/8/03, 1/13/03, 1/14/03, 1/15/03, 1/24/03, and 3/10/03.

A notice of completeness letter was mailed to the source on 11/13/02.

The source also submitted a letter on 11/7/02 stating the source name had changed from Premdor Corporation to Masonite Door Corporation. The name change has been incorporated into this renewal.

Emission Calculations

See Appendix A pages 1 through 6 of this document for detailed emissions calculations

Potential To Emit

Pursuant to 326 IAC 2-1.1-1(16), Potential to Emit is defined as "the maximum capacity of a stationary source to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or type or amount of material combusted, stored, or processed shall be treated as part of its design if the limitation is enforceable by the U. S. EPA."

This table reflects the PTE before controls. Control equipment is not considered federally enforceable until it has been required in a federally enforceable permit.

Pollutant	Potential To Emit (tons/year)	
PM	60	
PM-10	60	
SO ₂	0	

VOC	134
СО	5
NO _x	6

Note: For the purpose of determining Title V applicability for particulates, PM-10, not PM, is the regulated pollutant in consideration.

HAP's	Potential To Emit (tons/year)
Glycol Ethers	132
All other HAPs (see App. A)	< 1
TOTAL	132

- (a) The potential to emit (as defined in 326 IAC 2-1.1-1(16)) of VOC is equal to or greater than 100 tons per year. Therefore, the source is subject to the provisions of 326 IAC 2-7.
- (b) The potential to emit (as defined in 326 IAC 2-1.1-1(16)) of any single HAP is equal to or greater than ten (10) tons per year and the potential to emit (as defined in 326 IAC 2-7-1(29)) of a combination HAPs is greater than or equal to twenty-five (25) tons per year. Therefore, the source is subject to the provisions of 326 IAC 2-7.
- (c) Fugitive Emissions
 Since this type of operation is not one of the twenty-eight (28) listed source categories
 under 326 IAC 2-2 and since there are no applicable New Source Performance Standards
 that were in effect on August 7, 1980, the fugitive emissions are not counted toward
 determination of PSD and Emission Offset applicability.

Actual Emissions

The following table shows the actual emissions from the source. This information reflects the 2000 OAQ emission data.

Pollutant	Actual Emissions (tons/year)
PM	None Reported
PM-10	13
SO ₂	None Reported
VOC	21
СО	None Reported
NO _x	None Reported
HAP (specify)	None Reported

County Attainment Status

The source is located in Wayne County.

Pollutant	Status
PM-10	attainment
SO ₂	attainment
NO ₂	attainment
Ozone	attainment
co	attainment
Lead	attainment

- (a) Volatile organic compounds (VOC) are precursors for the formation of ozone. Therefore, VOC emissions are considered when evaluating the rule applicability relating to the ozone standards. Wayne County has been designated as attainment or unclassifiable for ozone. Therefore, VOC emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2 and 40 CFR 52.21.
- (b) Wayne County has been classified as attainment or unclassifiable for PM-10, SO₂, NO_x, CO, and Lead. Therefore, these emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2 and 40 CFR 52.21.

Part 70 Permit Conditions

This source is subject to the requirements of 326 IAC 2-7, pursuant to which the source has to meet the following:

- (a) Emission limitations and standards, including those operational requirements and limitations that assure compliance with all applicable requirements at the time of issuance of Part 70 permits.
- (b) Monitoring and related record keeping requirements which assume that all reasonable information is provided to evaluate continuous compliance with the applicable requirements.

Federal Rule Applicability

- (a) There are no New Source Performance Standards (NSPS)(326 IAC 12 and 40 CFR Part 60) applicable to this source.
- (b) There are no current National Emission Standards for Hazardous Air Pollutants (NESHAPs)(326 IAC 14 and 40 CFR Part 63) applicable to this source.
 - (1) The source manufactures metal doors. The surface coating of the metal door is in the Miscellaneous Metal Parts and Products source category. The source has ovens and heaters which are in the Industrial, Commercial, Institutional Boilers and Process Heaters source category. While the doors are mostly metal, each door includes wood and plastic. The surface coating of these parts is in the Wood Building Products and Plastic Parts source categories. All of these source categories have yet to have their NESHAPs promulgated.
 - (2) The Door Foam operation is not subject to the National Emission Standards for Hazardous Air Pollutants for Flexible Polyurethane Foam Production (NESHAP III). The Door Foam does not meet the definition of Flexible Polyurethane Foam or Rebond Foam.
- (c) The source is subject to section 112(j) MACT hammer requirements. The source has submitted a Part 1 application.
 - (1) The Permittee shall submit a Part 2 MACT Application in accordance with 40 CFR 63.52(e)(1). The Part 2 MACT Application shall meet the requirements of 40 CFR 63.53(b).
 - (2) Notwithstanding paragraph (1), the Permittee is not required to submit a Part 2 MACT Application if the Permittee no longer meets the applicability criteria of 40 CFR 63.50 by the application deadline in 40 CFR 63.52(e)(1). For example, the

Permittee would not have to submit a Part 2 MACT Application if, by the application deadline:

- (a) The source is no longer a major source of hazardous air pollutants, as defined in 40 CFR 63.2;
- (b) The source no longer includes one or more units in an affected source category for which the U.S. EPA failed to promulgate an emission standard by May 15, 2002; or
- (c) The MACT standard or standards for the affected source categories included at the source are promulgated.
- (3) Notwithstanding paragraph (1), pursuant to 40 CFR 63.56(a), the Permittee shall comply with an applicable promulgated MACT standard in accordance with the schedule provided in the MACT standard if the MACT standard is promulgated prior to the Part 2 MACT Application deadline or prior to the issuance of a permit with a case-by-case Section 112(j) MACT determination. The MACT requirements include the applicable General Provisions requirements of 40 CFR 63, Subpart A. Pursuant to 40 CFR 63.9(b), the Permittee shall submit an initial notification not later than 120 days after the effective date of the MACT, unless the MACT specifies otherwise. The initial notification shall be submitted to:

Indiana Department of Environmental Management Compliance Data Section, Office of Air Quality 100 North Senate Avenue, P.O. Box 6015 Indianapolis, Indiana 46206-6015

and

United States Environmental Protection Agency, Region V Director, Air and Radiation Division 77 West Jackson Boulevard Chicago, Illinois 60604-3590

(d) No units at this source are subject to Compliance Assurance Monitoring (CAM)(40 CFR Part 64. The two paint booths are considered one unit. The two paints booths, as one unit, have potential pre-control device emissions for VOC, a single HAP, and the combination of all HAPs equal to or greater than the major source threshold level. The source has no emission limits for theses pollutants. The source has no control device for these pollutants. Therefore, the requirements of 40 CFR 64, Compliance Assurance Monitoring, are not applicable to this source.

State Rule Applicability - Entire Source

326 IAC 1-5-2 (Emergency Reduction Plans)

The source has submitted an Emergency Reduction Plan (ERP) on 3/10/03. The ERP has been found to fulfill the requirements of 326 IAC 1-5-2 (Emergency Reduction Plans).

326 IAC 1-6-3 (Preventive Maintenance Plan)

The source has submitted a Preventive Maintenance Plan (PMP) on 1/15/03. This PMP has been verified to fulfill the requirements of 326 IAC 1-6-3 (Preventive Maintenance Plan).

326 IAC 1-7-3 (a) (Actual Stack Height Provisions)

The current stacks at the source are exempt from the provisions of 326 IAC 1-7-3 (a), since the source has less than twenty-five (25) tons per year of actual emissions (after controls) of PM and SO2.

326 IAC 2-2 (Prevention of Significant Deterioration)

The total source potential emissions of all criteria pollutants are less than 250 tons per year. Based on statements made by the source, a letter from an employee at the source, and research of local government agencies' files, the source was constructed between July 1977 and January 1980. The source has not conducted any modifications. Therefore the requirements of 326 IAC 2-2 (Prevention of Significant Deterioration) and 40 CFR 52.21 do not apply. The source is a minor source for PSD.

326 IAC 2-4.1-1 (New Source Toxics Control)

This source was constructed prior to July 1, 1997, therefore, this rule does not apply.

326 IAC 2-6 (Emission Reporting)

This source is subject to 326 IAC 2-6 (Emission Reporting), because it has the potential to emit more than one hundred (100) tons per year of VOC. Pursuant to this rule, the owner/operator of the source must annually submit an emission statement for the source. The annual statement must be received by July 1 of each year and contain the minimum requirement as specified in 326 IAC 2-6-4. The submittal should cover the period defined in 326 IAC 2-6-2(8)(Emission Statement Operating Year).

326 IAC 5-1 (Opacity Limitations)

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

- (a) Opacity shall not exceed an average of forty percent (40%) any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.
- (b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

State Rule Applicability - Individual Facilities

326 IAC 6-3-2(d) (Particulate Emission Limitations for Manufacturing Processes)

Pursuant to 326 IAC 6-3-2(d), particulate from the two (2) surface coating silos (Paint 1 and Paint 2) shall be controlled by the dry particulate filters, and the Permittee shall operate the control devices in accordance with manufacturer's specifications.

40 CFR 52 Subpart P (Indiana SIP).

Pursuant to 40 CFR Part 52 Subpart P, the particulate matter (PM) from the spray coating silos shall be limited by the following:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

 $E = 4.10 P^{0.67}$ where E = rate of emission in pounds per hour and P = process weight rate in tons per hour

Page 10 of 10 T177-16192-00068

Masonite Door Corporation Richmond, Indiana Permit Reviewer: Jed D. Wolkins

326 IAC 8-1-6 (New facilities: general reduction requirements)

326 IAC 8-1-6 does not apply to surface coating silos, identified as Paint 1 and Paint 2, even though their emissions are greater than twenty-five (25) tons per year, because they were constructed prior to the 1980 rule applicability.

326 IAC 8-2-9 (Miscellaneous Metal Coating)

The two (2) surface coating silos, identified as Paint 1 and Paint 2, although they have potential emissions greater than 25 tons per year, were constructed prior to 1980. Therefore, 326 IAC 8-2-9 (Miscellaneous Metal Coating Operations) does not apply.

326 IAC 8-6 (Organic Solvent Emission Limitations)

This source is subject to 326 IAC 8-6 because it was constructed between October 7, 1974 and January 1, 1980 and the potential VOC emissions are greater than 100 tons per year. However, the solvents in use are exempt per 326 IAC 8-6-2 (4). An change at the source that started the use of a non-exempt solvent would trigger the requirements of this section.

There are no other 326 IAC 8 rules that apply to the paint silos.

Compliance Requirements

Permits issued under 326 IAC 2-7are required to ensure that sources can demonstrate compliance with applicable state and federal rules on a more or less continuous basis. All state and federal rules contain compliance provisions, however, these provisions do not always fulfill the requirement for a more or less continuous demonstration. When this occurs IDEM, OAQ, in conjunction with the source, must develop specific conditions to satisfy 326 IAC 2-7-5. As a result, compliance requirements are divided into two sections: Compliance Determination Requirements and Compliance Monitoring Requirements.

Compliance Determination Requirements in Section D of the permit are those conditions that are found more or less directly within state and federal rules and the violation of which serves as grounds for enforcement action. If these conditions are not sufficient to demonstrate continuous compliance, they will be supplemented with Compliance Monitoring Requirements, also Section D of the permit. Unlike Compliance Determination Requirements, failure to meet Compliance Monitoring conditions would serve as a trigger for corrective actions and not grounds for enforcement action. However, a violation in relation to a compliance monitoring condition will arise through a source's failure to take the appropriate corrective actions within a specific time period.

The compliance monitoring requirements applicable to the surface coating silos Paint 1 and Paint 2 are as follows:

- (a) Daily inspections shall be performed to verify the placement, integrity and particle loading of the filters. To monitor the performance of the dry filters, weekly observations shall be made of the overspray from the surface coating silo vents C1 and C2 while one or more of the silos are in operation. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with Section C Compliance Monitoring Plan Failure to Take Response Steps, shall be considered a violation of this permit.
- (b) Monthly inspections shall be performed of the coating emissions from the vents C1 and C2 and the presence of overspray on the rooftops and the nearby ground. The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when a noticeable change in overspray emission or evidence of overspray emission is observed. The Compliance Response Plan shall be followed whenever a condition exists which should result in a response step. Failure to take response steps in accordance with

Page 11 of 10 T177-16192-00068

Masonite Door Corporation Richmond, Indiana Permit Reviewer: Jed D. Wolkins

Section C - Compliance Monitoring Plan - Failure to Take Response Steps, shall be considered a violation of this permit.

(c) Additional inspections and preventive measures shall be performed as prescribed in the Preventive Maintenance Plan.

These monitoring conditions are necessary because dry filter controls must operate properly to ensure compliance with 326 IAC 6-3 (Process Operations).

Conclusion

The operation of this metal door manufacturing plant shall be subject to the conditions of the attached proposed Part 70 Permit No. T177-16192-00068.

Appendix A: Emissions Calculations Particulate From Surface Coating Operations

Address City IN Zip: 305 Industrial Parkway, Richmond, IN 47674

TVOP: T177-16192-00068 Reviewer: Jed D. Wolkins Date: 10/23/02

Company Name: Masonite Door Corporation

Material	Density (Lb/Gal)	Weight % Volatile (H20 & Organics)	Weight % Water	Weight % Organics	Volume % Water	Volume % Non-Volatiles (solids)	Gal of Mat. (gal/unit)	Maximum (unit/hour)			Particulate Potential (ton/yr)	Transfer Efficiency
Paint 1												
C717	10.4	59.26%	50.5%	8.8%	62.6%	24.40%	0.066853	240.00			29.80	90%
Paint 2												
C717	10.4	59.26%	50.5%	8.8%	62.6%	24.40%	0.066853	240.00			29.80	90%

State Potential Emissions

Add worst case coating to all solvents

59.61

METHODOLOGY

Pounds of VOC per Gallon Coating less Water = (Density (lb/gal) * Weight % Organics) / (1-Volume % water)

Pounds of VOC per Gallon Coating = (Density (lb/gal) * Weight % Organics)

Potential VOC Pounds per Hour = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr)

Potential VOC Pounds per Day = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr) * (24 hr/day)

Potential VOC Tons per Year = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr) * (8760 hr/yr) * (1 ton/2000 lbs)

Particulate Potential Tons per Year = (units/hour) * (gal/unit) * (lbs/gal) * (1- Weight % Volatiles) * (1-Transfer efficiency) *(8760 hrs/yr) *(1 ton/2000 lbs)

Pounds VOC per Gallon of Solids = (Density (lbs/gal) * Weight % organics) / (Volume % solids)

Total = Worst Coating + Sum of all solvents used

Appendix A: Emissions Calculations VOC From Surface Coating Operations

Company Name: Masonite Door Corporation

Address City IN Zip: 305 Industrial Parkway, Richmond, IN 47674

TVOP: T177-16192-00068 Reviewer: Jed D. Wolkins Date: 10/23/02

Material	Density (Lb/Gal)	Weight % Volatile (H20 & Organics)	Weight % Water	Weight % Organics	Volume % Water	Volume % Non-Volatiles (solids)	Gal of Mat. (gal/unit)	Maximum (unit/hour)	Pounds VOC per gallon of coating less water	Pounds VOC per gallon of coating		Potential VOC pounds per day	Potential VOC tons per year	lb VOC/gal solids	Transfer Efficiency
Paint 1															
C721	9.8	64.54%	54.9%	9.6%	62.6%	24.40%	0.066853	240.00	2.52	0.94	15.11	362.65	66.18	3.86	90%
Paint 2															
C721	9.8	64.54%	54.9%	9.6%	62.6%	24.40%	0.066853	240.00	2.52	0.94	15.11	362.65	66.18	3.86	90%

State Potential Emissions

Add worst case coating to all solvents

30.22

725.29

132.37

METHODOLOGY

Pounds of VOC per Gallon Coating less Water = (Density (lb/gal) * Weight % Organics) / (1-Volume % water)

Pounds of VOC per Gallon Coating = (Density (lb/gal) * Weight % Organics)

Potential VOC Pounds per Hour = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr)

Potential VOC Pounds per Day = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr) * (24 hr/day)

Potential VOC Tons per Year = Pounds of VOC per Gallon coating (lb/gal) * Gal of Material (gal/unit) * Maximum (units/hr) * (8760 hr/yr) * (1 ton/2000 lbs)

Particulate Potential Tons per Year = (units/hour) * (gal/unit) * (lbs/gal) * (1- Weight % Volatiles) * (1-Transfer efficiency) *(8760 hrs/yr) *(1 ton/2000 lbs)

Pounds VOC per Gallon of Solids = (Density (lbs/gal) * Weight % organics) / (Volume % solids)

Total = Worst Coating + Sum of all solvents used

Appendix A: Emission Calculations HAP Emission Calculations

Company Name: Masonite Door Corporation Address City IN Zip: 305 Industrial Parkway

TVOP #: T177-16192-00068 Permit Reviewer: Jed D. Wolkins

Date: 10/22/02

Material	Density (Lb/Gal)	Gallons of Material (gal/unit)	Maximum (unit/hour)			Weight % Formaldehyde	Weight % Benzene	Weight % Hexane	Weight % Glycol Ethers	Weight % Methanol	Xylene Emissions (ton/yr)	Toluene Emissions (ton/yr)	Formaldehyde Emissions (ton/yr)		Hexane Emissions (ton/yr)	Glycol Ethers Emissions (ton/yr)	Methanol Emissions (ton/yr)
Paint 1																	
C721	9.81	0.066853	240.00	0.00%	0.00%	0.00%	0.00%	0.00%	9.50%	0.00%	0.00	0.00	0.00	0.00	0.00	65.49	0.00
Paint 2																	
C721	9.81	0.066853	240.00	0.00%	0.00%	0.00%	0.00%	0.00%	9.50%	0.00%	0.00	0.00	0.00	0.00	0.00	65.49	0.00

Total State Potential Emissions 0.00 0.00 0.00 0.00 130.99 0.00

METHODOLOGY

HAPS emission rate (tons/yr) = Density (lb/gal) * Gal of Material (gal/unit) * Maximum (unit/hr) * Weight % HAP * 8760 hrs/yr * 1 ton/2000 lbs

Appendix A: Emission Calculations VOC and HAP Emission Calculations

Company Name: Masonite Door Corporation Address City IN Zip: 305 Industrial Parkway TVOP #: T177-16192-00068

Permit Reviewer: Jed D. Wolkins

Date: 12/12/02

Alkaline Cleaner

Usage	Density	Weight %	Weight %	Weight %	Weight %	Potential	Potential
gallons	lbs/gal	Volatile	H2O	Organics	Glycol	VOC tons	Glycol Ethers
per year		rolatilo	1.20	0.9400	Ethers	per year	tons per year
1773	8.3	0.977	0.8	0.177	0.15	1.30235715	1.1036925

METHODOLOGY

VOC emission rate (tons/yr) = Density (lb/gal) * Weight % Organics * Usage (gal/yr) * 1 ton/2000 lbs HAPS emission rate (tons/yr) = Density (lb/gal) * Weight % HAP * Usage (gal/yr) * 1 ton/2000 lbs Note: Alkaline Cleaner is used to flush the disk and paint line.

Door Foam Process

Maximum	thickness	width	length	Tproc	VP MDI	MW MDI	k MDI	Vair	Potential
units per hour	inches	inches	inches	K	mm Hg			cubic feet	HAP/VOC
								per year	lbs per year
150	1.75	36	96	302.4	1.79E-05	250.2	0.63	4599000	0.04283915

METHODOLOGY

Vair (cubic feet/yr) = Maximum (unit/hr) * thickness (inches) * width (inches) * length (inches) * 8760 hrs/yr

HAPS/VOC emission rate (tons/yr) = Vair (cf/yr) * VP MDI (mm Hg) * k MDI * MW MDI * 273.15 / (359 * Tproc (K) * 760) * 1 ton/2000 lbs

Note: Methodology is based on Alliance for the Polyurethanes Industry "MDI/Polymeric MDI Emissions Reporting Guidelines For the Polyurethane Industry",pages 4-35 to 4-36 and App. A and B.

4405

4-4-1

Combustion Sources

Appendix A: Emissions Calculations Natural Gas Combustion Only

	MM BTU/HR <100	Compustio	n Sources
Sr	mall Industrial Boiler	Source	mmBtu/hr
Company Name:	Masonite Door Corporation	Curing oven	1.5
Address City IN Zip:	305 Industrial Parkway, Richmond, IN 47674	Space Heater	0.1
TVOP:	T177-16192-00068	Space Heater	0.1
Reviewer:	Jed D. Wolkins	Space Heater	0.1
Date:	10/23/02	Wash Tank He	1.5
		Wash Tank He	1.5
		Dry off oven	1.5
Potential Thro	pughput	AMU North P	5
MMCF/yr		AMU North B	0.65
		AMU South 1	1.2
120.0		AMU South 2	1.2
	Company Name: Address City IN Zip: TVOP: Reviewer: Date: Potential Thro	Small Industrial Boiler Company Name: Masonite Door Corporation Address City IN Zip: 305 Industrial Parkway, Richmond, IN 47674 TVOP: T177-16192-00068 Reviewer: Jed D. Wolkins Date: 10/23/02 Potential Throughput MMCF/yr	Small Industrial Boiler Company Name: Masonite Door Corporation Address City IN Zip: 305 Industrial Parkway, Richmond, IN 47674 TVOP: T177-16192-00068 Space Heater Reviewer: Jed D. Wolkins Date: 10/23/02 Wash Tank He Dry off oven Potential Throughput AMU North P MMCF/yr AMU North B AMU South 1

		Pollutant			totai	14.35
	PM*	PM10*	SO2	NOx	VOC	CO
Emission Factor in lb/MMCF	1.9	7.6	0.6	100.0	5.5	84.0
				**see below		
Potential Emission in tons/yr	0.1	0.5	0.0	6.0	0.3	5.0

Dallusans

Methodology

All emission factors are based on normal firing.

MMBtu = 1,000,000 Btu

MMCF = 1,000,000 Cubic Feet of Gas

Potential Throughput (MMCF) = Heat Input Capacity (MMBtu/hr) x 8,760 hrs/yr x 1 MMCF/1,000 MMBtu

Emission Factors are from AP 42, Chapter 1.4, Tables 1.4-1, 1.4-2, 1.4-3, SCC #1-02-006-02, 1-01-006-02, 1-03-006-02, and 1-03-006-03 (SUPPLEMENT D 3/98)

Emission (tons/yr) = Throughput (MMCF/yr) x Emission Factor (lb/MMCF)/2,000 lb/ton

Note: Check the applicable rules and test methods for PM and PM10 when using the above emission factors to confirm that the correct factor is used (i.e., condensable included/not included).

See page 6 for HAPs emissions calculations.

^{*}PM emission factor is filterable PM only. PM10 emission factor is condensable and filterable PM10 combined.

^{**}Emission Factors for NOx: Uncontrolled = 100, Low NOx Burner = 50, Low NOx Burners/Flue gas recirculation = 32

Appendix A: Emissions Calculations Natural Gas Combustion Only MM BTU/HR <100 Small Industrial Boiler

HAPs Emissions

Company Name: Masonite Door Corporation

Address City IN Zip: 305 Industrial Parkway, Richmond, IN 47674

TVOP: T177-16192-00068 Reviewer: Jed D. Wolkins

Date: 10/23/02

HAPs - Organics

Emission Factor in lb/MMcf	Benzene	Dichlorobenzene	Formaldehyde	Hexane	Toluene
	2.1E-03	1.2E-03	7.5E-02	1.8E+00	3.4E-03
Potential Emission in tons/yr	1.260E-04	7.201E-05	4.500E-03	1.080E-01	2.040E-04

HAPs - Metals

Emission Factor in lb/MMcf	Lead	Cadmium	Chromium	Manganese	Nickel
	5.0E-04	1.1E-03	1.4E-03	3.8E-04	2.1E-03
Potential Emission in tons/yr	3.000E-05	6.601E-05	8.401E-05	2.280E-05	1.260E-04

Methodology is the same as page 1.

The five highest organic and metal HAPs emission factors are provided above. Additional HAPs emission factors are available in AP-42, Chapter 1.4.